

Q8 Auto 15 S

Full synthetic automatic transmission fluid with extended drain capability

Description

Q8 Auto 15 S is a superior performance full synthetic automatic transmission fluid, designed for heavy duty vehicles. The product is especially formulated for trucks, buses and military equipment in severe operating conditions, because of its exceptional viscosity index and extended drain capability. It meets the specifications of ZF transmissions, Allison Transmission, Mercedes-Benz and Voith.

Applications

Q8 Auto 15 S is specifically formulated for severe operating conditions. It is specifically designed for ZF Ecomat Transmissions requiring ZF TE-ML 14C, ZF TE-ML 20C specification. The product is also formulated for Voith 55.6336, MAN 339 V-2/Z-3, Allison TES-295, Allison TES-389, Dexron III G and MB 236.91.

Benefits

- Full synthetic formulation to provide an extreme thermal stability.
- Superior protection against wear and extends component life.
- Superior gear protection under heavy duty conditions.
- Exceptional wear protection under heavy duty operating conditions.
- Exceptional internal friction reduction.

Specifications, recommendations and approvals

Allison	TES-295	MB	236.91
Allison	TES-389	Voith	H55.6336.xx
Allison	TES-468	ZF	TE-ML 14C
GM	Dexron III G	ZF	TE-ML 16S
MAN	339 Type V2	ZF	TE-ML 20C
MAN	339 Type Z3	ZF	TE-ML 25C

Color code blue = officially approved

Properties

	<i>Method</i>	<i>Unit</i>	<i>Typical</i>
Density, 15 °C	D 4052	g/ml	0,85
Kinematic Viscosity, 40 °C	D 445	mm ² /s	37.4
Kinematic Viscosity, 100 °C	D 445	mm ² /s	7.4
Viscosity Index	D 2270	-	171
Brookfield Viscosity, -40 °C	D 2983	Pa.s	8.5
Pour Point	D 97	°C	-48
Flash Point, COC	D 92	°C	236

The figures above are not a specification. They are typical figures obtained within production tolerances.