

Q8 Bizet AW 460

Chain and chainsaw oil with excellent performance

Description

Q8 Bizet AW 460 is a chain and chainsaw oil with an excellent performance and a low pour point. It contains well balanced extreme pressure additives that offer a low oil consumption. Q8 Bizet AW 460 has a strong adhesive oil film that leads to a longer lifetime of the chain slides. Its components are carefully selected with no harmful or unpleasant odours.

Applications

Q8 Bizet AW 460 is used in chains and slides of chainsaws. It is also perfect for chains, slides and guides in industrial applications.

Benefits

Improves the durability of the equipment thanks to its characteristics

Low oil consumption which leads to a lower maintenance cost

Features

Excellent adhesiveness

Outstanding anti-wear characteristics

Excellent thermal durability

Outstanding friction diminution

Neutral in odor

Specifications & Approvals

ISO 6743-1 L-AC

Properties

	Method	Unit	Typical
ISO Viscosity Grade	-	-	460
Density, 15 °C	D 4052	g/ml	0,899
Colour	D 1500	-	L 2.5
Kinematic Viscosity, 40 °C	D 445	mm ² /s	460
Kinematic Viscosity, 100 °C	D 445	mm ² /s	31.0
Viscosity Index	D 2270	-	97
Total Acid Number	D 974	mg KOH/g	0.37
Pour Point	D 97	°C	-12
Flash Point, COC	D 92	°C	296
Copper Strip, 3 h, 100 °C	D 130	-	1
Texture	Visual	-	Stringy
Four Ball Wear, 392 N, 75 °C, 1200 rpm	D 4172	mm	0.4

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

Q8 Bizet AW 460 should not be used for lubricating the engine of the chain saw.