

## Q8 Gluck S

Advanced heat transfer oil

### Description

Q8 Gluck S is an advanced heat transfer oil with a well selected, highly refined paraffinic base oil. It is used for indirect closed heat transfer systems and has a high heat transfer performance over a wide temperature range. Q8 Gluck S has a long service life thanks to its oxidation stability and low carbon cracking. Its carbon deposition is reduced to a minimum to guarantee a cleaner system.

### Applications

Q8 Gluck S is used in closed heat transfer systems operating at oil film temperatures of max 330°C.

### Benefits

Improves the durability of the equipment thanks to its characteristics

### Features

Excellent heat dissipation  
Outstandingly heat-resistant  
High flash point  
Low residue forming  
Excellent thermal persistence

### Specifications & Approvals

ISO 6743-12 Q

### Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,873
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	35.61
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	5.77
Viscosity Index	D 2270	-	102
Pour Point	D 97	°C	-15
Flash Point, COC	D 92	°C	230
Flash Point, P-M	D 93	°C	min. 200
Boiling Point	-	°C	337

The figures above are not a specification. They are typical figures obtained within production tolerances.

### Remarks

Excellent low temperature flow properties (-15°C)