

Q8 Halley 68

Zinc-free hydraulic oil for an extensive use in severe circumstances

Description

Q8 Halley 68 is zinc-free and ideal for a broad range of temperatures and perfect for severe circumstances. The high oxidation stability results in a long service life of the oil. Q8 Halley 68, suitable for servo hydraulic applications, has an advanced filterability and demulsibility, which limits the deposit in hydraulic valves to a minimum.

Applications

Q8 Halley 68 is suitable for severe circumstances and applications in a broad range of temperatures such as robotic hydraulics, assembly lines, bulldozers, industrial applications (e.g. injection moulding machines, presses, ...) and harbour applications like locks.

Benefits

Decreased downtime thanks to increased maintenance efficiency

Extends service life time thus minimal costs and maximal efficiency

Features

Does not contain zinc

Exceptionally high viscosity index

Outstanding filtration characteristics

Excellent reduction of oil oxidation

Extreme capability to separate entrained water from oil

Exceptionally suitable for use in all seasons

Specifications & Approvals

Bosch Rexroth
DIN

RE 90220 notes
51524-3 HVLP

ISO

11158 HV

Properties

	Method	Unit	Typical
ISO Viscosity Grade	-	-	68
Density, 15 °C	D 4052	g/ml	0,879
Colour	D 1500	-	L 0.5
Kinematic Viscosity, 40 °C	D 445	mm ² /s	66.63
Kinematic Viscosity, 100 °C	D 445	mm ² /s	12.36
Viscosity Index	D 2270	-	187
Total Acid Number	D 664	mg KOH/g	0.15 after 1000h
Total Acid Number	D 974	mg KOH/g	0.11
Pour Point	D 97	°C	-39
Flash Point, COC	D 92	°C	194
Emulsion, Distilled Water, 54.4 °C	D 1401	-	40-40-0 (10 min)
Foam, 5 min blowing, seq. 1-2-3	D 892	ml	0/20/0
Foam, 10 min settling, seq. 1-2-3	D 892	ml	0/0/0
Rust Test, Proc. A and B, 24 h	D 665	-	pass
Copper Strip, 3 h, 100 °C	D 130	-	1a
FZG Test, A/8.3/90	DIN 51354	load stage	12

The figures above are not a specification. They are typical figures obtained within production tolerances.