

Q8 Handel 32

Zinc-based hydraulic oil with very high viscosity index

Description

Q8 Handel 32 is an excellent zinc-based hydraulic oil that is suitable for a wide range of temperatures and applications. Thanks to its very high viscosity index of >180, the zinc-based oil has exceptional flow properties. The high oxidation stability assures an extended drain interval and lubricant life. Q8 Handel 32 is used in demanding applications that require very high viscosity index oils.

Applications

Q8 Handel 32 is used in all season applications, off-highway equipment. It is also applied in industries and applications requiring high viscosity index oils, such as in paper, steel, cement, mining industry.

Benefits

Lower downtime and an improved maintenance efficiency

Extends service life time thus minimal costs and maximal efficiency

Features

Zinc included technology

Exceptionally high viscosity index

Optimum air release

Outstandingly resistant to oil deterioration

Exceptionally suitable for use in all seasons

Optimum separation of water

Specifications & Approvals

Bosch Rexroth	RE 90220 notes	ISO	11158 HV
DIN	51524-3 HVLP	Swedish Standard	SS 155434 AM
Eaton Brochure	03-401-2010		

Properties

	Method	Unit	Typical
ISO Viscosity Grade	-	-	32
Density, 15 °C	D 4052	g/ml	0,872
Colour	D 1500	-	L 1.0
Kinematic Viscosity, 40 °C	D 445	mm ² /s	32.30
Kinematic Viscosity, 100 °C	D 445	mm ² /s	6.95
Viscosity Index	D 2270	-	184
Pour Point	D 97	°C	-48
Total Acid Number	D 974	mg KOH/g	0.57
Total Acid Number	D 664	mg KOH/g	0.1 after 1000h
Flash Point, COC	D 92	°C	178
Emulsion, Distilled Water, 54.4 °C	D 1401	-	40-40-0(15 min)
Foam, 5 min blowing, seq. 1-2-3	D 892	ml	0/20/100
Foam, 10 min settling, seq. 1-2-3	D 892	ml	0/0/0
Rust Test, Proc. A and B, 24 h	D 665	-	pass
Copper Strip, 3 h, 100 °C	D 130	-	1a
FZG Test, A/8.3/90	DIN 51354	load stage	12

The figures above are not a specification. They are typical figures obtained within production tolerances.