

Q8 Heller 100

Advanced zinc-based hydraulic oil with high viscosity index

Description

Q8 Heller 100 is suitable for a broad range of applications and temperatures. The high viscosity index of > 140 exceeds the industrial standard which results in an oil with outstanding flow properties. The high oxidation stability leads to extended drain intervals and lubricant life. Q8 Heller 100 is used for demanding applications that require high viscosity index oils.

Applications

Q8 Heller 100 is suitable for all season applications such as off-highway equipment. It is also used in industries and applications requiring high viscosity index oils, like paper, steel, cement or mining industry.

Benefits

Extensive oil drain interval for a longer lubricant lifetime

Lower downtime and an improved maintenance efficiency

Features

Outstanding oxidation stability

Highly appropriate for use in a wide range of temperatures

Excellent high viscosity index

High protection against wear

Optimum separation of water

Specifications & Approvals

Afnor		ISO	11158 HV
DIN	51524-3 HVLP		

Properties

	Method	Unit	Typical
ISO Viscosity Grade	-	-	100
Density, 15 °C	D 4052	g/ml	0,882
Kinematic Viscosity, 40 °C	D 445	mm ² /s	100
Kinematic Viscosity, 100 °C	D 445	mm ² /s	14.3
Viscosity Index	D 2270	-	142
Pour Point	D 97	°C	-30
Flash Point, COC	D 92	°C	248
Emulsion, Distilled Water, 54.4 °C	D 1401	-	40-40-0(15)
Foam, 5 min blowing, seq. 1-2-3	D 892	ml	10/0/10
Foam, 10 min settling, seq. 1-2-3	D 892	ml	0/0/0
Rust Test, Proc. A and B, 24 h	D 665	-	pass

The figures above are not a specification. They are typical figures obtained within production tolerances.