

Q8 Heller 22

Advanced zinc-based hydraulic oil with high viscosity index

Description

Q8 Heller 22 is suitable for an extensive range of applications and temperatures. The high viscosity index of > 160 exceeds the industrial standard which results in an oil with outstanding flow properties. Thanks to the high oxidation stability, drain intervals and lubricant life are significantly extended. Q8 Heller 22 is used for demanding applications that require high viscosity index oils.

Applications

Q8 Heller 22 is suitable for all season applications such as off-highway equipment. It is also used in industries and applications requiring high viscosity index oils, like paper, steel, cement or mining industry.

Benefits

Extensive oil drain interval for a longer lubricant lifetime

Lower downtime and an improved maintenance efficiency

Features

Outstanding oxidation stability

Highly appropriate for use in a wide range of temperatures

Excellent high viscosity index

High protection against wear

Optimum separation of water

Specifications & Approvals

Afnor
DIN

51524-3 HVLP

ISO

11158 HV

Properties

	Method	Unit	Typical
ISO Viscosity Grade	-	-	22
Density, 15 °C	D 4052	g/ml	0,858
Kinematic Viscosity, 40 °C	D 445	mm ² /s	22.0
Kinematic Viscosity, 100 °C	D 445	mm ² /s	4.98
Viscosity Index	D 2270	-	161
Pour Point	D 97	°C	-36
Flash Point, COC	D 92	°C	190
Emulsion, Distilled Water, 54.4 °C	D 1401	-	40-40-0(5)
Foam, 5 min blowing, seq. 1-2-3	D 892	ml	50/20/50
Foam, 10 min settling, seq. 1-2-3	D 892	ml	0/0/0
Rust Test, Proc. A and B, 24 h	D 665	-	pass
Copper Strip, 3 h, 100 °C	D 130	-	1

The figures above are not a specification. They are typical figures obtained within production tolerances.