

Q8 Hoffmeister 46

Zinc- and detergent-based hydraulic oil with high viscosity index

Description

Q8 Hoffmeister 46 is a superior zinc-based hydraulic oil with extensive detergent and dispersant functionalities. This oil keeps the hydraulic systems clean without losing the hydraulic properties and helps to disperse contaminants, water and other deposits. Q8 Hoffmeister 46 has a high viscosity index (>150) and exceeds the industrial standard DIN HLVP (VI 140) and ISO HV.

Applications

Q8 Hoffmeister 46 is perfect for usage for hydraulic systems in off-road applications and mobile construction equipment. Thanks to its detergent functionalities, this oil is the ideal solution for hydraulic systems where water and pollution can be a problem. It can be used in the most extreme temperatures: from high to low.

Benefits

Minimizes downtime which leads to a higher maintenance efficiency

Extends service life time thus minimal costs and maximal efficiency

Features

Outstanding emulsification of entrained water

Excellent cleaning properties

Optimum anti-corrosion characteristics

High viscosity index

Excellently recommended in a wide range of temperatures

Zinc included technology

Specifications & Approvals

DIN	51524-3 HVLPD	ISO	11158 HV
------------	---------------	------------	----------

Properties

	Method	Unit	Typical
ISO Viscosity Grade	-	-	46
Density, 15 °C	D 4052	g/ml	0,874
Colour	D 1500	-	L 1.0
Kinematic Viscosity, 40 °C	D 445	mm ² /s	46.0
Kinematic Viscosity, 100 °C	D 445	mm ² /s	8.15
Viscosity Index	D 2270	-	152
Pour Point	D 97	°C	-39
Flash Point, COC	D 92	°C	218
Foam, 5 min blowing, seq. 1-2-3	D 892	ml	5/10/5
Foam, 10 min settling, seq. 1-2-3	D 892	ml	0/0/0
Rust Test, Proc. A and B, 24 h	D 665	-	pass
Copper Strip, 3 h, 100 °C	D 130	-	1

The figures above are not a specification. They are typical figures obtained within production tolerances.