

## Q8 Holst 22

Advanced zinc-free hydraulic oil

### Description

Q8 Holst 22 is a zinc-free oil that is a perfect fit for a wide range of operational applications and for industrial equipment. Q8 Holst 22 has an advanced filterability and demulsibility what makes it reliable for sensitive hydraulic servo systems. Thanks to its thermal and oxidation stability, this oil guarantees a long lubricant life time.

### Applications

Q8 Holst 22 is suitable for all kinds of systems, general industrial hydraulic applications and other industrial applications (low charged gears, pumps, compressors, bearings). It is also applied in sensitive hydraulic servo systems that require advanced demulsibility and filterability.

### Benefits

Decreased downtime thanks to increased maintenance efficiency

### Features

Zinc excluded technology

Optimum wear protection

Outstanding filterability

Highly fit for different operations

### Specifications & Approvals

**DIN** 51524-2 HLP **ISO** 11158 HM

### Properties

	Method	Unit	Typical
ISO Viscosity Grade	-	-	22
Density, 15 °C	D 4052	g/ml	0,863
Colour	D 1500	-	L 1.0
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	22.0
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	4.28
Viscosity Index	D 2270	-	98
Total Acid Number	D 974	mg KOH/g	0.20
Pour Point	D 97	°C	-21
Flash Point, COC	D 92	°C	202
Emulsion, Distilled Water, 54.4 °C	D 1401	-	40-40-0(5)
Emulsion, Distilled Water, 82.2 °C	D 1401	-	
Foam, 5 min blowing, seq. 1-2-3	D 892	ml	10/20/10
Foam, 10 min settling, seq. 1-2-3	D 892	ml	0/0/0
Rust Test, Proc. A and B, 24 h	D 665	-	pass
Oxidation stability, Time to 2.0 TAN	D 943	hrs	>2500
Copper Strip, 3 h, 100 °C	D 130	-	1

The figures above are not a specification. They are typical figures obtained within production tolerances.