

Q8 Huygens 46

Excellent zinc-free detergent hydraulic oil with high viscosity index

Description

The Q8 Huygens 46 is an excellent zinc-free hydraulic oil with extensive detergent and dispersant functionalities. This oil keeps the hydraulic systems clean without losing the hydraulic properties and helps to disperse contaminants, water and other deposits. The Q8 Huygens 46 has a high viscosity index (>150) and outstanding filterability properties.

Applications

The Q8 Huygens 46 is perfect for usage for hydraulic systems in off-road applications and mobile equipment. Thanks to its detergent functionalities, this oil is the ideal solution for hydraulic systems where water and pollution can be a problem. It is also applied in sensitive hydraulics servo systems and robotics industry. It can be used in the most extreme temperatures.

Benefits

Decreased downtime thanks to increased maintenance efficiency

Extensive oil drain interval for a longer lubricant lifetime

Features

Emulsifies entrained water

Excellent cleaning properties

Highly suitable for applications in a broad temperature spectrum

Zinc excluded technology

High viscosity index

Outstanding oxidation stability

Specifications & Approvals

DIN

51524-3 HVLPD

ISO

11158 HV

Properties

	Method	Unit	Typical
ISO Viscosity Grade	-	-	46
Density, 15 °C	D 4052	g/ml	0,873
Colour	D 1500	-	L 1.0
Kinematic Viscosity, 40 °C	D 445	mm ² /s	46.0
Kinematic Viscosity, 100 °C	D 445	mm ² /s	8.36
Viscosity Index	D 2270	-	159
Total Acid Number	D 974	mg KOH/g	0.3
Pour Point	D 97	°C	-36
Flash Point, COC	D 92	°C	222
Foam, 5 min blowing, seq. 1-2-3	D 892	ml	0/10/0
Foam, 10 min settling, seq. 1-2-3	D 892	ml	0/0/0
Rust Test, Proc. A and B, 24 h	D 665	-	pass
Copper Strip, 3 h, 100 °C	D 130	-	1
Oxidation stability, Time to 2.0 TAN	D 943	hrs	>2500
FZG Test, A/8.3/90	DIN 51354	load stage	>12

The figures above are not a specification. They are typical figures obtained within production tolerances.