

## Q8 Mozart TM 20 SAE 40

High performance trunk piston diesel engine lubricant

### Description

Q8 Mozart TM is a high performance trunk piston diesel engine lubricant for highly rated medium speed diesel engines operating on distillate fuels or HFO.

### Applications

For all turbo-charged medium speed trunk piston diesel engines in use as marine propulsion engines, auxiliary engines and PowerGen applications.

#### Features

##### Lower operational costs

#### Benefits

Extended oil life due to exceptional viscosity control in combination with superior base number retention over long period of time

##### Engine cleanliness

Superior clean engine technology that minimizes deposit and sludge build-up throughout the engine

##### Enhanced technology

Developed with superior quality base oils and exceptional additive technology, giving superior oxidation- and thermal stability over prolonged periods of time

### Specifications & Approvals

API

CF

Caterpillar

#### Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,898
Viscosity Grade	-	-	SAE 40
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	132
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	13.6
Viscosity Index	D 2270	-	98
Total Base Number	D 2896	mg KOH/g	20
Pour Point	D 97	°C	-12
Flash Point, P-M	D 93	°C	214
Sulfated Ash	D 874	% mass	2.5

The figures above are not a specification. They are typical figures obtained within production tolerances.