

## Q8 Rembrandt EP 1

Advanced lithium extreme pressure grease

### Description

Q8 Rembrandt EP 1 is a multi-purpose lithium grease with extreme pressure properties and is temperature resistant up to 130°C. This lithium grease is based on mineral oil and has optimum pumpability at low temperature thanks to its smooth structure. The advanced roll stability of the Q8 Rembrandt EP 1, the high anti-wear properties and rust protection lead to a long service life of the grease.

### Applications

Q8 Rembrandt EP 1 is used in industrial and automotive applications. It is suitable for centralised lubrication systems. Q8 Rembrandt EP 1 is highly recommended for highly loaded plain- and anti-friction bearings, bushings and pins in draglines, bulldozers, tractors, excavators, trucks, hoisting equipment, winches etc.

### Benefits

Improves the durability of the equipment thanks to its characteristics

### Features

Extreme pressure characteristics

Advanced mechanical stability

Highly appropriate for use in a wide range of temperatures

Optimum anti-rust characteristics

### Specifications & Approvals

DIN

51502 KP1K-30

ISO

6743 L-XCCFB1

### Properties

	Method	Unit	Typical
Colour	Visual	-	Brown
Consistency, NLGI No.	NLGI	-	NLGI 1
Penetration, Worked, 25 °C, 60 strokes	D 217	0.1 mm	319
Kin. Viscosity Base Oil at 40 °C	D 445	mm <sup>2</sup> /s	200
Dropping Point	D 566	°C	205
Copper Corrosion, 100 °C, 24 h	D 4048	-	pass
Four Ball Test, Weld Load	IP 239	N	2450

The figures above are not a specification. They are typical figures obtained within production tolerances.