

## Q8 Rembrandt EP 3

Advanced lithium extreme pressure grease

### Description

Q8 Rembrandt EP 3 is a multi-purpose lithium grease with extreme pressure properties. It has an NLGI grade 3 for optimum protection against water penetration and prevents grease leakages from vertical mounted bearings. Q8 Rembrandt EP 3 is temperature resistant up to 130°C and has an optimum rust-protection.

### Applications

Q8 Rembrandt EP 3 is used in industrial and automotive applications. It is suitable for bearings mounted on vertical shafts. Q8 Rembrandt EP 3 is highly recommended for highly loaded plain- and anti-friction bearings, bushings and pins in draglines, bulldozers, tractors, excavators, trucks, hoisting equipment, winches etc.

### Benefits

Improves the durability of the equipment thanks to its characteristics

### Features

Extreme pressure characteristics

Advanced mechanical stability

Highly appropriate for use in a wide range of temperatures

Optimum anti-rust characteristics

### Specifications & Approvals

DIN 51502 KP3K-20 ISO 6743 L-XBCFB3

### Properties

	Method	Unit	Typical
Colour	Visual	-	Brown
Consistency, NLGI No.	NLGI	-	NLGI 3
Penetration, Worked, 25 °C, 60 strokes	D 217	0.1 mm	235
Kin. Viscosity Base Oil at 40 °C	D 445	mm <sup>2</sup> /s	280
Dropping Point	D 566	°C	>180
Copper Corrosion, 100 °C, 24 h	D 4048	-	pass
Kin. Viscosity Base Oil at 100 °C	D 445	mm <sup>2</sup> /s	20
Four Ball Test, Weld Load	IP 239	N	2600

The figures above are not a specification. They are typical figures obtained within production tolerances.