

Q8 Rubens EM 2

Lithium complex grease for electric motor bearings

Description

Q8 Rubens EM 2 is a lithium complex grease and the primary choice for different types of electric motor bearing applications. The mineral oil-based grease is used in a wide temperature range and has outstanding low start-up torque properties. Q8 Rubens EM 2 has outstanding roll and mechanical stability and an excellent rust-protection. Its smooth structure leads to an easy pumpability.

Applications

Q8 Rubens EM 2 is used as a versatile grease for a variety of industrial applications. It is highly recommended for bearing lubrication of electric motors and high speed applications.

Benefits

Extensive oil drain interval for a longer lubricant lifetime

Minimizes downtime which leads to a higher maintenance efficiency

Features

Excellently high dropping point

Superior anti-rust characteristics

Excellently suitable for applications in a broad temperature spectrum

Outstanding roll stability

Excellent high load carrying capacity

Optimum grease flow properties

Specifications & Approvals

DIN	51502 KP2N-30	ISO	6743 L-XCDHB2
------------	---------------	------------	---------------

Properties

	Method	Unit	Typical
Colour	Visual	-	Yellowish
Consistency, NLGI No.	NLGI	-	2
Penetration, Worked, 25 °C, 60 strokes	D 217	0.1 mm	295
Kin. Viscosity Base Oil at 40 °C	D 445	mm ² /s	110
Dropping Point	D 566	°C	>260
Copper Corrosion, 100 °C, 24 h	D 4048	-	1b
Four Ball Test, Weld Load	IP 239	N	2600
Four Ball Wear, 392 N, 75 °C, 1200 rpm	D 4172	mm	0.5

The figures above are not a specification. They are typical figures obtained within production tolerances.