

## Q8 Scarlatti 46

High performance compressor oil

### Description

Q8 Scarlatti 46 is a high performance compressor oil based on selected premium (Group II) base fluids. This product is developed for use in all reciprocating-, rotary- and vane type compressors. It is designed as part of the Q8Oils clean technology program to ensure superior compressor cleanliness in combination with long oil life. It meets the challenges of the latest generation compressors.

### Applications

All reciprocating- (piston), rotary screw- and vane type compressors Single- and multistage air compressors in both stationary- and mobile applications

#### Features

Lower operational costs

Own product development

Enhanced technology

#### Benefits

Extended quality all-round product for every type of compressor and vacuum pump

Formulated with high quality Group II base oil

Outstanding deposit control to keep the compressor clean, even under severe conditions

### Specifications & Approvals

<b>DIN</b>	51506 VDL	<b>ISO</b>	6743-3 DAG
<b>ISO</b>	6743-3 DAA	<b>ISO</b>	6743-3 DAH
<b>ISO</b>	6743-3 DAB	<b>ISO</b>	6743-3 DVA

### Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,865
ISO Viscosity Grade	-	-	46
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	46.0
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	6.9
Viscosity Index	D 2270	-	105
Total Acid Number	D 974	mg KOH/g	0.12
Pour Point	D 97	°C	-18
Flash Point, COC	D 92	°C	228
Colour	D 1500	-	L 0.5
Ash	D 482	% mass	<0.01
Sulfated Ash	D 874	% mass	0.02
Emulsion, Distilled Water, 54.4 °C	D 1401	-	40-40-0(5)
Foam, 10 min settling, seq. 1-2-3	D 892	ml	0/0/0
Foam, 5 min blowing, seq. 1-2-3	D 892	ml	10/20/20
Rust Test, Proc. A and B, 24 h	D 665	-	pass
FZG Test, A/8.3/90	DIN 51354	load stage	11

The figures above are not a specification. They are typical figures obtained within production tolerances.