

Q8 T 3000

Superior transmission and hydraulic oil for agriculture and construction

Description

Q8 T 3000 is an exceptional combined transmission and hydraulic oil for agricultural and construction equipment. This oil has an extreme performance stability to temperatures, limits brake noises and counteracts foaming. Q8 T 3000 has superior lubrication properties under hard loads, anti-rust and anti-corrosion properties and is compatible with conventional rubber materials.

Applications

Q8 T 3000 is used in agricultural, off-highway and construction equipment that require special lubricant protection of the drive-axle. It is applied as a rear axle lubricant, oil-immersed brake/clutch fluid, transmission lubricant or hydraulic fluid.

Benefits

- Limits wet brake noise while limiting friction plate wear.
- Excellent transmission lubrication.
- Excellent response of hydraulic components.
- Excellent anti-foaming properties.
- Superb compatibility with conventional elastomers.

Specifications, recommendations and approvals

API	GL-4	Ford	M2C 86-B
Allison	C-3	Komatsu Dresser	B06-0002
Case	MS 1207	Landini	UTTO
Case	MS 1209	Massey Ferguson	CMS M 1127
Case	UK/David Brown	Massey Ferguson	CMS M 1135
Caterpillar	TO-2	Massey Ferguson	CMS M 1141
Fiat	AF 87	Same Deutz Fahr	

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,885
Kinematic Viscosity, 40 °C	D 445	mm ² /s	84.8
Kinematic Viscosity, 100 °C	D 445	mm ² /s	10.61
Viscosity Index	D 2270	-	109
Brookfield Viscosity, -26 °C	D 2983	Pa.s	31
Pour Point	D 97	°C	-30
Flash Point, P-M	D 93	°C	220

The figures above are not a specification. They are typical figures obtained within production tolerances.