

Q8 TO-4 Fluid 40

Transmission fluid for Caterpillar

Description

Q8 TO-4 Fluid 40 is an outstanding transmission fluid, especially formulated for Caterpillar. This product offers excellent protection at low temperature conditions and facilitates easy starting. It contains additives to prevent oxidation and deposit formation. The oil is suitable for use in equipment where TO-4 fluids are prescribed.

Applications

Q8 TO-4 Fluid 40 is especially formulated for Caterpillar, but also suitable in power shift transmissions, final drives, hydrostatic transmissions, torque converters and hydraulics in heavy duty vehicles. The fluid can be used in off-highway, construction and agricultural equipment.

Benefits

- Superior gear protection under shock load conditions.
- Exceptional wear protection under heavy duty operating conditions.
- Superior axle wear protection.
- Superior protection against rust and corrosion.

Specifications, recommendations and approvals

Allison	C-4	Eaton/Fuller	
Caterpillar	TO-4	Komatsu Dresser	Micro-Clutch
DANA		ZF	TE-ML 03C

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,897
Viscosity Grade	-	-	SAE 40
Kinematic Viscosity, 40 °C	D 445	mm ² /s	135.7
Kinematic Viscosity, 100 °C	D 445	mm ² /s	13.9
Viscosity Index	D 2270	-	99
Pour Point	D 97	°C	-30
Flash Point, COC	D 92	°C (°F)	262

The figures above are not a specification. They are typical figures obtained within production tolerances.