

Q8 Verdi 100

Multi-purpose circulating oil

Description

Q8 Verdi 100 is an advanced multi-purpose circulating oil with a long service life. It has a high chemical and thermal stability and protects against rust and corrosion. Q8 Verdi 100 has optimum lubricating characteristics and water resistant properties.

Applications

Q8 Verdi 100 is used in hydro turbines, pumps, valves and other applications that require a long service life. It is applied in a variety of industrial systems that don't need anti-wear performance. Q8 Verdi 100 is highly recommended for plain and rolling bearings, vacuum pumps, hydraulic pumps and air compressor applications.

Benefits

Extensive lubricant applications so limited products needed

Extends service life time thus minimal costs and maximal efficiency

Features

Highly suitable for a wide range of application

Outstanding oxidation stability

Optimum anti-corrosion characteristics

Optimum separation of water

Specifications & Approvals

DIN	51506 VBL	DIN	51524-1 HL
DIN	51515-1 L-TD	ISO	6743-2 F
DIN	51517-2 CL		

Properties

	Method	Unit	Typical
ISO Viscosity Grade	-	-	100
Density, 15 °C	D 4052	g/ml	0,883
Kinematic Viscosity, 40 °C	D 445	mm ² /s	100
Kinematic Viscosity, 100 °C	D 445	mm ² /s	11.2
Viscosity Index	D 2270	-	97
Pour Point	D 97	°C	-27
Flash Point, COC	D 92	°C	254
Colour	D 1500	-	L 1.5
Emulsion, Distilled Water, 82.2 °C	D 1401	-	40-40-0(10)
Foam, 5 min blowing, seq. 1-2-3	D 892	ml	10/20/10
Foam, 10 min settling, seq. 1-2-3	D 892	ml	0/0/0
Rust Test, Proc. A and B, 24 h	D 665	-	pass
Copper Strip, 3 h, 100 °C	D 130	-	1

The figures above are not a specification. They are typical figures obtained within production tolerances.